

	SAFETY DATA SHEET	Page : 1 / 21
		Revision nr : 4.0
	Bellows Adhesive	Issue date : 13/09/2023
		Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : Bellows Adhesive
 UFI : MMRV-N0C9-H001-K538
 Product code : 8M0133959
 Document no. : 766-01-0024S
 (Original SDS: US-029-0302Q 2019)

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
 Main use category : Industrial use, Professional use, Consumer use
 Use of the substance/mixture : Adhesives, sealants

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Brunswick Marine EMEA
 Parc industriel de Petit-Rechain, Avenue Mercury 8
 4800 Verviers - Belgium
 T +32 (0)87 32 32 11
bme.compliance@brunswick.com

1.4. Emergency telephone number

Emergency number : 0032 3 575 55 55
 This telephone number is available 24 hours per day, 7 days per week.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
 Eye Irrit. 2 H319
 STOT SE 3 H336
 Aquatic Chronic 3 H412

Full text of H- and EUH-statements: see section 16

	SAFETY DATA SHEET	Page : 2 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word

: Danger

Contains

: acetone; propan-2-one; propanone

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents and container to an approved waste disposal plant.

Extra phrases

: EUH066 - Repeated exposure may cause skin dryness or cracking.

Child-resistant fastening

: Not applicable

Tactile warning

: Applicable

2.3. Other hazards

Other hazards

: Vapours can form explosive mixtures with air. Results of PBT and vPvB assessment : Not applicable.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

	SAFETY DATA SHEET	Page : 3 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone; propan-2-one; propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index) 606-001-00-8	40 – 70	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
salicylic acid	(CAS-No.) 69-72-7 (EC-No.) 200-712-3 (EC Index) 607-732-00-5	< 3	Repr. 2, H361d Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
zinc oxide	(CAS-No.) 1314-13-2 (EC-No.) 215-222-5 (EC Index) 030-013-00-7	< 2,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice	: First aider: Pay attention to self-protection!. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance.
Inhalation	: Remove casualty to fresh air and keep warm and at rest. In case of doubt or persistent symptoms, consult always a physician.
Skin contact	: Remove contaminated clothing and shoes. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.
Eyes contact	: Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of doubt or persistent symptoms, consult always a physician.
Ingestion	: Rinse mouth thoroughly with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: May cause drowsiness or dizziness. The following symptoms may occur: Irritation. Headache. Pain. Coughing, sneezes.
Skin contact	: The following symptoms may occur: Repeated exposure may cause skin dryness or cracking.
Eyes contact	: Causes serious eye irritation. The following symptoms may occur: erythema (redness). Swelling of tissue. Pain. Tears. Corneal opacity. Impairment of vision.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: carbon dioxide (CO ₂), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media	: Strong water jet.

	SAFETY DATA SHEET	Page : 4 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

5.2. Special hazards arising from the substance or mixture

Specific hazards : Highly flammable liquid and vapour. Heating will cause a rise in pressure with a risk of bursting. Vapours may form explosive mixture with air. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂). Nitrogen oxides. Hydrocarbons.

5.3. Advice for firefighters

Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.

Other information : Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel : Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately earthed. Use explosion-proof equipment. Use only non-sparking tools.

6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation. Cover the spilled liquid product with foam to slow down evaporation.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

	SAFETY DATA SHEET	Page : 5 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools.
Hygiene measures	: Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Storage of flammable liquids. Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage. Take precautionary measures against static discharge.
Heat and ignition sources	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Special rules on packaging	: Tactile warning. Containers which are opened should be properly resealed and kept upright to prevent leakage.
Packaging materials	: Keep only in the original container.

7.3. Specific end use(s)

Adhesives, sealants.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

acetone; propan-2-one; propanone (67-64-1)		
EU	IOEL TWA	1210 mg/m ³
EU	IOEL TWA [ppm]	500 ppm
Austria	MAK (OEL TWA)	1200 mg/m ³
Austria	MAK (OEL TWA) [ppm]	500 ppm
Austria	MAK (OEL STEL)	4800 mg/m ³
Austria	MAK (OEL STEL) [ppm]	2000 ppm
Belgium	OEL TWA	594 mg/m ³
Belgium	OEL TWA [ppm]	246 ppm
Belgium	OEL STEL	1187 mg/m ³
Belgium	OEL STEL [ppm]	492 ppm
Bulgaria	OEL TWA	600 mg/m ³
Bulgaria	OEL STEL	1400 mg/m ³
Croatia	GVI (OEL TWA) [1]	1210 mg/m ³
Croatia	GVI (OEL TWA) [2]	500 ppm

	SAFETY DATA SHEET		Page : 6 / 21
			Revision nr : 4.0
	Bellows Adhesive		Issue date : 13/09/2023
			Supersedes : 21/02/2023
			766-01-0024S (Original SDS: US-029-0302Q 2019)

acetone; propan-2-one; propanone (67-64-1)		
Croatia	Acetone (blood, End of shift): 20 mg/l (0,34 mmol/l) Acetone (Urine, End of shift): 39 mmol/mol Creatinine	
Cyprus	OEL TWA	1210 mg/m ³
Cyprus	OEL TWA [ppm]	500 ppm
Czech Republic	PEL (OEL TWA)	800 mg/m ³
Denmark	OEL TWA [1]	600 mg/m ³
Denmark	OEL TWA [2]	250 ppm
Denmark	OEL STEL	1200 mg/m ³
Denmark	OEL STEL [ppm]	500 ppm
Estonia	OEL TWA	1210 mg/m ³
Estonia	OEL TWA [ppm]	500 ppm
Finland	HTP (OEL TWA) [1]	1200 mg/m ³
Finland	HTP (OEL TWA) [2]	500 ppm
Finland	HTP (OEL STEL)	1500 mg/m ³
Finland	HTP (OEL STEL) [ppm]	630 ppm
France	VME (OEL TWA)	1210 mg/m ³ (restrictive limit)
France	VME (OEL TWA) [ppm]	500 ppm (restrictive limit)
France	VLE (OEL C/STEL)	2420 mg/m ³ (restrictive limit)
France	VLE (OEL C/STEL) [ppm]	1000 ppm (restrictive limit)
Germany	Occupational exposure limit value (mg/m ³) (TRGS900)	1200 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	Occupational exposure limit value (ppm) (TRGS900)	500 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	Biological limit value	80 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift
Gibraltar	OEL TWA	1210 mg/m ³
Gibraltar	OEL TWA [ppm]	500 ppm
Greece	OEL TWA	1780 mg/m ³
Greece	OEL STEL	3560 mg/m ³
Hungary	AK (OEL TWA)	1210 mg/m ³
Ireland	OEL TWA [1]	1210 mg/m ³
Ireland	OEL TWA [2]	500 ppm
Ireland	OEL STEL	3630 mg/m ³ (calculated)
Ireland	OEL STEL [ppm]	1500 ppm (calculated)
Italy	OEL TWA	1210 mg/m ³
Italy	OEL TWA [ppm]	500 ppm
Latvia	OEL TWA	1210 mg/m ³
Latvia	OEL TWA [ppm]	500 ppm
Lithuania	IPRV (OEL TWA)	1210 mg/m ³

	SAFETY DATA SHEET	Page : 7 / 21
		Revision nr : 4.0
	Bellows Adhesive	Issue date : 13/09/2023
		Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

acetone; propan-2-one; propanone (67-64-1)		
Lithuania	IPRV (OEL TWA) [ppm]	500 ppm
Lithuania	TPRV (OEL STEL)	2420 mg/m ³
Lithuania	TPRV (OEL STEL) [ppm]	1000 ppm
Luxembourg	OEL TWA	1210 mg/m ³
Luxembourg	OEL TWA [ppm]	500 ppm
Malta	OEL TWA	1210 mg/m ³
Malta	OEL TWA [ppm]	500 ppm
Netherlands	TGG-8u (OEL TWA)	1210 mg/m ³
Netherlands	TGG-8u (OEL TWA) [ppm]	500 ppm
Netherlands	TGG-15min (OEL STEL)	2420 mg/m ³
Netherlands	TGG-15min (OEL STEL) [ppm]	1 ppm
Poland	NDS (OEL TWA)	600 mg/m ³
Poland	NDSch (OEL STEL)	1800 mg/m ³
Portugal	OEL TWA	1210 mg/m ³ (indicative limit value)
Portugal	OEL TWA [ppm]	500 ppm (indicative limit value)
Portugal	OEL STEL [ppm]	750 ppm
Romania	OEL TWA	1210 mg/m ³
Romania	OEL TWA [ppm]	500 ppm
Slovakia	NPHV (OEL TWA) [1]	1210 mg/m ³
Slovakia	NPHV (OEL TWA) [2]	500 ppm
Slovenia	OEL TWA	1210 mg/m ³
Slovenia	OEL TWA [ppm]	500 ppm
Slovenia	OEL STEL	2420 mg/m ³
Slovenia	OEL STEL [ppm]	1000 ppm
Spain	VLA-ED (OEL TWA) [1]	1210 mg/m ³ (indicative limit value)
Spain	VLA-ED (OEL TWA) [2]	500 ppm (indicative limit value)
Sweden	NGV (OEL TWA)	600 mg/m ³
Sweden	NGV (OEL TWA) [ppm]	250 ppm
Sweden	KTV (OEL STEL)	1200 mg/m ³
Sweden	KTV (OEL STEL) [ppm]	500 ppm
United Kingdom	WEL TWA (OEL TWA) [1]	1210 mg/m ³
United Kingdom	WEL TWA (OEL TWA) [2]	500 ppm
United Kingdom	WEL STEL (OEL STEL)	3620 mg/m ³
United Kingdom	WEL STEL (OEL STEL) [ppm]	1500 ppm
Norway	Grenseverdi (OEL TWA) [1]	295 mg/m ³
Norway	Grenseverdi (OEL TWA) [2]	125 ppm
Norway	Korttidsverdi (OEL STEL)	368,75 mg/m ³ (value calculated)
Norway	Korttidsverdi (OEL STEL) [ppm]	156,25 ppm (value calculated)
Switzerland	MAK (OEL TWA) [1]	1200 mg/m ³
Switzerland	MAK (OEL TWA) [2]	500 ppm

	SAFETY DATA SHEET	Page : 8 / 21
		Revision nr : 4.0
	Bellows Adhesive	Issue date : 13/09/2023
		Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

acetone; propan-2-one; propanone (67-64-1)		
Switzerland	KZGW (OEL STEL)	2400 mg/m ³
Switzerland	KZGW (OEL STEL) [ppm]	1000 ppm
Australia	OES TWA [1]	1185 mg/m ³
Australia	OES TWA [2]	500 ppm
Australia	OES STEL	2375 mg/m ³
Australia	OES STEL [ppm]	1000 ppm
Canada (Quebec)	VECD (OEL STEL)	2380 mg/m ³
Canada (Quebec)	VECD (OEL STEL) [ppm]	1000 ppm
Canada (Quebec)	VEMP (OEL TWA)	1190 mg/m ³
Canada (Quebec)	VEMP (OEL TWA) [ppm]	500 ppm
USA - ACGIH	ACGIH OEL TWA [ppm]	250 ppm
USA - ACGIH	ACGIH OEL STEL [ppm]	500 ppm
USA - IDLH	IDLH [ppm]	2500 ppm (10% LEL)
USA - NIOSH	NIOSH REL TWA	590 mg/m ³
USA - NIOSH	NIOSH REL TWA [ppm]	250 ppm
USA - OSHA	OSHA PEL TWA [1]	2400 mg/m ³
USA - OSHA	OSHA PEL TWA [2]	1000 ppm
zinc oxide (1314-13-2)		
Austria	MAK (OEL TWA)	5 mg/m ³ (respirable fraction, smoke)
Belgium	OEL TWA	10 mg/m ³ (dust)
		5 mg/m ³ (fume)
		5 mg/m ³ (aerosol and vapor)
Belgium	OEL STEL	10 mg/m ³ (fume)
		10 mg/m ³ (aerosol and vapor)
Bulgaria	OEL TWA	5 mg/m ³
Bulgaria	OEL STEL	10 mg/m ³
Croatia	GVI (OEL TWA) [1]	5 mg/m ³
Croatia	KGVI (OEL STEL)	10 mg/m ³
Czech Republic	PEL (OEL TWA)	2 mg/m ³
Denmark	OEL TWA [1]	4 mg/m ³
		4 mg/m ³ (fume)
Denmark	OEL STEL	8 mg/m ³
		8 mg/m ³ (fume)
Estonia	OEL TWA	5 mg/m ³
Finland	HTP (OEL TWA) [1]	2 mg/m ³ (fume)
Finland	HTP (OEL STEL)	10 mg/m ³ (fume)
France	VME (OEL TWA)	5 mg/m ³ (fume)
		10 mg/m ³ (dust)
Greece	OEL TWA	5 mg/m ³ (fume)
Greece	OEL STEL	10 mg/m ³ (fume)
Hungary	AK (OEL TWA)	5 mg/m ³ (respirable dust)
Hungary	CK (OEL STEL)	20 mg/m ³ (respirable dust)
Ireland	OEL TWA [1]	2 mg/m ³ (fume; respirable fraction)

	SAFETY DATA SHEET	Page : 9 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

zinc oxide (1314-13-2)		
Ireland	OEL STEL	10 mg/m ³ (fume; respirable)
Latvia	OEL TWA	0,5 mg/m ³
Lithuania	IPRV (OEL TWA)	5 mg/m ³
Poland	NDS (OEL TWA)	5 mg/m ³ (inhalable fraction)
Poland	NDSch (OEL STEL)	10 mg/m ³ (inhalable fraction)
Portugal	OEL TWA	2 mg/m ³ (respirable fraction)
Portugal	OEL STEL	10 mg/m ³ (respirable fraction)
Romania	OEL TWA	5 mg/m ³ (fume)
Romania	OEL STEL	10 mg/m ³ (fume)
Slovakia	NPHV (OEL TWA) [1]	1 mg/m ³ (fume)
Slovakia	NPHV (OEL C)	1 mg/m ³
Slovenia	OEL TWA	5 mg/m ³ (respirable fraction, fume)
Slovenia	OEL STEL	20 mg/m ³ (respirable fraction, fume)
Spain	VLA-ED (OEL TWA) [1]	2 mg/m ³ (respirable fraction)
Spain	VLA-EC (OEL STEL)	10 mg/m ³
Sweden	NGV (OEL TWA)	5 mg/m ³ (total dust)
Norway	Grenseverdi (OEL TWA) [1]	5 mg/m ³
Norway	Korttidsverdi (OEL STEL)	10 mg/m ³ (value calculated)
Switzerland	MAK (OEL TWA) [1]	3 mg/m ³ (respirable dust, smoke)
Switzerland	KZGW (OEL STEL)	3 mg/m ³ (respirable dust, smoke)
Australia	OES TWA [1]	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-inhalable dust) 5 mg/m ³ (fume)
Australia	OES STEL	10 mg/m ³ (fume)
Canada (Quebec)	VECD (OEL STEL)	10 mg/m ³ (respirable dust)
Canada (Quebec)	VEMP (OEL TWA)	2 mg/m ³ (respirable dust)
USA - ACGIH	ACGIH OEL TWA	2 mg/m ³ (respirable particulate matter)
USA - ACGIH	ACGIH OEL STEL	10 mg/m ³ (respirable particulate matter)
USA - IDLH	IDLH	500 mg/m ³
USA - NIOSH	NIOSH REL TWA	5 mg/m ³ (dust and fume)
USA - NIOSH	NIOSH REL STEL	10 mg/m ³ (fume)
USA - NIOSH	NIOSH REL C	15 mg/m ³ (dust)
USA - OSHA	OSHA PEL TWA [1]	5 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

Additional information

: Recommended monitoring procedures :. Personal air monitoring. Room air monitoring

	SAFETY DATA SHEET	Page : 10 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

8.2. Exposure controls

Engineering measure(s)	: Provide adequate ventilation. Organisational measures to prevent/limit releases, dispersion and exposure. See Section 7 for information on safe handling. Use only outdoors or in a well-ventilated area. Take precautionary measures against static discharges. Ensure equipment is adequately earthed. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.
Personal protective equipment	: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Hand protection	: Wear chemically resistant gloves (tested to EN374) . Suitable material: Butyl caoutchouc (butyl rubber). Breakthrough time : Not determined. Thickness : Not determined. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Use suitable eye protection (EN166): goggles
Body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: ABEK (EN14387). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)
Thermal hazard protection	: Not required for normal conditions of use. Use dedicated equipment.
Environmental exposure controls	: Avoid release to the environment. Comply with applicable Community environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: dark brown.
Odour	: Solvent. (Sharp).
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting / freezing point	: Not applicable
Freezing point	: No data available
Initial boiling point and boiling range	: ≥ 56 °C
Flash point	: -20 °C (closed cup)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Not applicable,liquid
Vapour pressure	: ≤ 185 mmHg (20 °C)
Vapour density	: 2 (Air = 1.0)
Relative density	: 0,91
Density	: 0,91 mg/l

	SAFETY DATA SHEET	Page : 11 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

Solubility	: Water: < 10 %
Partition coefficient n-octanol/water	: No data available
Kinematic viscosity	: 1500 – 3200 cPs (27 °C)
Dynamic viscosity	: No data available
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Explosive limits	: 2,6 – 12,8 %
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 569 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour. Reference to other sections: 10.4 & 10.5.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air. No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. See Section 7 for information on safe handling.

10.5. Incompatible materials

oxidising substances. See Section 7 for information on safe handling.

10.6. Hazardous decomposition products

Reference to other sections 5.2.

	SAFETY DATA SHEET	Page : 12 / 21
		Revision nr : 4.0
	Bellows Adhesive	Issue date : 13/09/2023
		Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

acetone; propan-2-one; propanone (67-64-1)	
LD50/oral/rat	5800 mg/kg
LD50/dermal/rat	> 10000 mg/kg
LD50/dermal/rabbit	> 15700 mg/kg
LD50 dermal	> 10000 mg/kg
LC50/inhalation/4h/rat	50100 mg/m ³ (Exposure time: 8 h)
LC50 Inhalation - Rat (Vapours)	76 mg/l/4h
salicylic acid (69-72-7)	
LD50/oral/rat	891 mg/kg
LD50/dermal/rat	> 2 g/kg
LC50/inhalation/4h/rat	> 900 mg/m ³ (Exposure time: 1 h)
zinc oxide (1314-13-2)	
LD50/oral/rat	> 5000 mg/kg
LD50/dermal/rat	> 2000 mg/kg
LC50/inhalation/4h/rat	> 5700 mg/l/4h
LD50, mouse, oral	7950 mg/kg
LC50, mouse, Inhalation	2500 mg/m ³

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
pH: Not applicable

Serious eye damage/irritation : Causes serious eye irritation.
pH: Not applicable

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Bellows Adhesive	
Kinematic viscosity	1500 – 3200 mm ² /s (27 °C)

Other information : Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4. Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

	SAFETY DATA SHEET	Page : 13 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2 Other information

Other information

: Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4, Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties

: Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute)

: Not classified

Hazardous to the aquatic environment, long-term (chronic)

: Harmful to aquatic life with long lasting effects.

acetone; propan-2-one; propanone (67-64-1)

LC50 - Fish [1]	4,74 – 6,33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
LC50 - Fish [2]	6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	10294 – 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)

salicylic acid (69-72-7)

EC50 - Crustacea [1]	870 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
----------------------	--

zinc oxide (1314-13-2)

LC50 - Fish [1]	1,55 mg/l (Exposure time: 96 h - Species: Danio rerio [static])
LC50 - Fish [2]	1,793 mg/l (Danio Rerio)
EC50 - Crustacea [1]	2,6 mg/l (Daphnia Magna)
EC50 72h - Algae [1]	0,136 mg/l (Pseudokirchnerella subcapitata)
NOEC (additional information)	NOEC, Fish 101ug/L (M.bahia)

12.2. Persistence and degradability

Bellows Adhesive	
Persistence and degradability	No additional information available.

	SAFETY DATA SHEET	Page : 14 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

acetone; propan-2-one; propanone (67-64-1)	
---	--

Biodegradation	78 % (28 days)
----------------	----------------

zinc oxide (1314-13-2)	
-------------------------------	--

Persistence and degradability	Not applicable, inorganic compounds.
-------------------------------	--------------------------------------

12.3. Bioaccumulative potential

Bellows Adhesive	
-------------------------	--

Partition coefficient n-octanol/water	No data available
Bioaccumulative potential	No additional information available.

acetone; propan-2-one; propanone (67-64-1)	
---	--

BCF - Fish [1]	(0.69 dimensionless)
Partition coefficient n-octanol/water	-0,24

salicylic acid (69-72-7)	
---------------------------------	--

BCF - Fish [1]	(1000 dimensionless)
Partition coefficient n-octanol/water	2,25 (at 25 °C)

12.4. Mobility in soil

Bellows Adhesive	
-------------------------	--

Mobility in soil	No data available
Ecology - soil	No data available.

12.5. Results of PBT and vPvB assessment

Bellows Adhesive	
-------------------------	--

Results of PBT assessment	Not applicable
---------------------------	----------------

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : Not applicable

12.7. Other adverse effects

Other adverse effects : No data available

	SAFETY DATA SHEET	Page : 15 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Avoid release to the environment. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations. Packaging contaminated by the product : Do not pierce or burn, even after use. Never use pressure to empty container.

European waste catalogue
(2001/573/EC, 75/442/EEC, 91/689/EEC)

: This material and its container must be disposed of as hazardous waste
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
1133	1133	1133	1133	1133
14.2. UN proper shipping name				
ADHESIVES	ADHESIVES	Adhesives	ADHESIVES	ADHESIVES
Transport document description				
UN 1133 ADHESIVES, 3, II, (D/E)	UN 1133 ADHESIVES, 3, II	UN 1133 Adhesives, 3, II	UN 1133 ADHESIVES, 3, II	UN 1133 ADHESIVES, 3, II
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR) : F1
Special provisions : 640D
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001

	SAFETY DATA SHEET	Page : 16 / 21
		Revision nr : 4.0
	Bellows Adhesive	Issue date : 13/09/2023
		Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

Special packing provisions (ADR) : PP1
 Mixed packing provisions (ADR) : MP19
 Portable tank and bulk container instructions (ADR) : T4
 Portable tank and bulk container special provisions (ADR) : TP1, TP8
 Tank code (ADR) : LGBF
 Vehicle for tank carriage : FL
 Transport category (ADR) : 2
 Special provisions for carriage - Operation (ADR) : S2, S20
 Hazard identification number (Kemler No.) : 33
 Orange plates :



Tunnel restriction code : D/E
 EAC code : •3YE

- Transport by sea

Limited quantities (IMDG) : 5 L
 Excepted quantities (IMDG) : E2
 Packing instructions (IMDG) : P001
 Special packing provisions (IMDG) : PP1
 IBC packing instructions (IMDG) : IBC02
 Tank instructions (IMDG) : T4
 Tank special provisions (IMDG) : TP1, TP8
 EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-D
 Stowage category (IMDG) : B
 Properties and observations (IMDG) : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

- Air transport

PCA Excepted quantities (IATA) : E2
 PCA Limited quantities (IATA) : Y341
 PCA limited quantity max net quantity (IATA) : 1L
 PCA packing instructions (IATA) : 353
 PCA max net quantity (IATA) : 5L
 CAO packing instructions (IATA) : 364
 CAO max net quantity (IATA) : 60L
 Special provisions (IATA) : A3
 ERG code (IATA) : 3L

- Inland waterway transport

Classification code (ADN) : F1

	SAFETY DATA SHEET	Page : 17 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

Special provisions (ADN) : 640D
 Limited quantities (ADN) : 5 L
 Excepted quantities (ADN) : E2
 Equipment required (ADN) : PP, EX, A
 Ventilation (ADN) : VE01
 Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID) : F1
 Special provisions (RID) : 640D
 Limited quantities (RID) : 5L
 Excepted quantities (RID) : E2
 Packing instructions (RID) : P001, IBC02, R001
 Special packing provisions (RID) : PP1
 Mixed packing provisions (RID) : MP19
 Portable tank and bulk container instructions (RID) : T4
 Portable tank and bulk container special provisions (RID) : TP1, TP8
 Tank codes for RID tanks (RID) : LGBF
 Transport category (RID) : 2
 Colis express (express parcels) (RID) : CE7
 Hazard identification number (RID) : 33

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Listed on REACH Annex XVII (Restriction Conditions). The following restrictions are applicable:

3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Bellows Adhesive ; acetone; propan-2-one; propanone
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Bellows Adhesive ; acetone; propan-2-one; propanone
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Bellows Adhesive
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	acetone; propan-2-one; propanone

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

	SAFETY DATA SHEET		Page : 18 / 21
			Revision nr : 4.0
			Issue date : 13/09/2023
	Bellows Adhesive		Supersedes : 21/02/2023
			766-01-0024S (Original SDS: US-029-0302Q 2019)

VOC content : 569 g/l

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

France

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4331.text	Liquides inflammables de catégorie 2 ou catégorie 3 à l'exclusion de la rubrique 4330. La quantité totale susceptible d'être présente dans les installations y compris dans les cavités souterraines étant :		
4331.1	1. Supérieure ou égale à 1000 t Quantité seuil bas au sens de l'article R. 511-10 : 5 000 t. Quantité seuil haut au sens de l'article R. 511-10 : 50 000 t.	A	2
4331.2	2. Supérieure ou égale à 100 t mais inférieure à 1000 t Quantité seuil bas au sens de l'article R. 511-10 : 5 000 t. Quantité seuil haut au sens de l'article R. 511-10 : 50 000 t.	E	
4331.3	3. Supérieure ou égale à 50 t mais inférieure à 100 t Quantité seuil bas au sens de l'article R. 511-10 : 5 000 t. Quantité seuil haut au sens de l'article R. 511-10 : 50 000 t.	DC	

Germany

Regulatory reference : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
German storage class (LGK) : LGK 3 - Flammable liquids

	SAFETY DATA SHEET	Page : 19 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

Hazardous Incident Ordinance (12. BlmSchV)

- : Listed in the 12. BlmSchV (Annex I) under: 1.2.5.3
Quantity threshold for operational area under § 1 para. 1
- Sentence 1: 5000000 kg
 - Sentence 2: 50000000 kg

Netherlands

- Waterbezwaarlijkheid : A (3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic environment
- SZW-lijst van kankerverwekkende stoffen : None of the components are listed
- SZW-lijst van mutagene stoffen : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : salicylic acid is listed

Denmark

- Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
- Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Norway

- This safety datasheet has been prepared according to Norwegian legislation. : FOR 2002-07-16 nr 1139: Forskrift om klassifisering, merking mv. av farlige kjemikalier; Forskrift om klassifisering, merking og emballering av stoffer og stoffblandinger (CLP); FOR 2008-05-30 nr 516: Forskrift om registrering, vurdering, godkjenning og begrensning av kjemikalier (REACH-forskriften)

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes:

15	Explosive Precursors Regulation	Added	
----	---------------------------------	-------	--

Abbreviations and acronyms:

	ABM = Algemene beoordelingsmethodiek
	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
	ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
	CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods Code
	LEL = Lower Explosive Limit/Lower Explosion Limit
	UEL = Upper Explosion Limit/Upper Explosive Limit
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	BTT = Breakthrough time (maximum wearing time)

	SAFETY DATA SHEET	Page : 20 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

	DMEL = Derived Minimal Effect level
	DNEL = Derived No Effect Level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate
	EWC = European waste catalogue
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	NA = Not applicable
	NOEC = No observed effect concentration
	NOEL: no-observed-effect level
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	N.O.S. = Not Otherwise Specified
	OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	PNEC = Predicted No Effect Concentration
	Quantitative structure-activity relationship (QSAR)
	STOT = Specific Target Organ Toxicity
	TWA = time weighted average
	VOC = Volatile organic compounds
	WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Training advice : Training staff on good practice.

Other information : Classification - Assessment method: CLP Calculation method (Article 9).

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

	SAFETY DATA SHEET	Page : 21 / 21
		Revision nr : 4.0
		Issue date : 13/09/2023
	Bellows Adhesive	Supersedes : 21/02/2023
		766-01-0024S (Original SDS: US-029-0302Q 2019)

Repr. 2	Reproductive toxicity, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.