

	SAFETY DATA SHEET	Page : 1 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name/designation : Extreme Gear Lube SAE 85W-90
 Product code : 8M0133995, 8M0133997
 Document no. : 766-01-0276S
 (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
 Main use category : Industrial use, Professional use, Consumer use
 Use of the substance/mixture : Lubricants

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Brunswick Marine EMEA
 Parc industriel de Petit-Rechain, Avenue Mercury 8
 BE 4800 Verviers
 Belgium
 T +32 (0)87 32 32 11
bme.compliance@brunswick.com

1.4. Emergency telephone number

Emergency number : 0032 3 575 55 55
 This telephone number is available 24 hours per day, 7 days per week.

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment – Chronic H412
 Hazard, Category 3
 Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

	SAFETY DATA SHEET		Page : 2 / 24
			Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90		Issue date : 18/12/2025
			Supersedes : 21/02/2023
			766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word	: -
Hazard statements (CLP)	: H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P273 - Avoid release to the environment. P501 - Dispose of contents and container to an approved waste disposal plant.
Extra phrases	: EUH208 - Contains Polysulfides, di-tert-Bu, Calcium Sulfonate, Amines, C12-14-tert-alkyl. May produce an allergic reaction.
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

2.3. Other hazards

Other hazards	: Results of PBT and vPvB assessment : Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII.
---------------	--

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Calcium Sulfonate	CAS-No.: 64521-08-0 EC-No.: 682-721-6	< 0,5	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Amines, C12-14-tert-alkyl	CAS-No.: 68955-53-3 EC-No.: 273-279-1	< 0,5	Acute Tox. 4 (Oral), H302 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 2 (Inhalation), H330 (ATE=0,05 mg/l/4h) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Distillates (petroleum), solvent-dewaxed heavy paraffinic	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6	0 – 0,13455	Carc. 1B, H350

	SAFETY DATA SHEET	Page : 3 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Polysulfides, di-tert-Bu	CAS-No.: 68937-96-2 EC-No.: 273-103-3 EC Index-No.: - REACH-no: 01-2119540515-43-XXXX	<1	Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
(Z)-octadec-9-enylamine	CAS-No.: 112-90-3 EC-No.: 204-015-5 EC Index-No.: 612-283-00-3	< 0,5	Acute Tox. 4 (Oral), H302 (ATE=1689 mg/kg bodyweight) Asp. Tox. 1, H304 STOT SE 3, H335 STOT RE 2, H373 Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
Naphtha (petroleum), hydrotreated heavy (conc. benzene > 0,1%) substance with a Community workplace exposure limit	CAS-No.: 64742-48-9 EC-No.: 265-150-3 EC Index-No.: 649-327-00-6	0,014	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411 Repr. 2, H361fd Muta. 1B, H340 Carc. 1B, H350
ethyl acrylate substance with a Community workplace exposure limit	CAS-No.: 140-88-5 EC-No.: 205-438-8 EC Index-No.: 607-032-00-X	≤ 0,0002	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 (ATE=1120 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1800 mg/kg bodyweight) Acute Tox. 3 (Inhalation:vapour), H331 (ATE=9 mg/l) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335

Specific concentration limits:

Substance name	Product identifier	Specific concentration limits (%)
ethyl acrylate	CAS-No.: 140-88-5 EC-No.: 205-438-8 EC Index-No.: 607-032-00-X	(5 ≤ C < 100) STOT SE 3; H335 (5 ≤ C < 100) Skin Irrit. 2; H315 (5 ≤ C < 100) Eye Irrit. 2; H319

Full text of H- and EUH-statements: see section 16

	SAFETY DATA SHEET	Page : 4 / 24
		Revision nr : 4.0
		Issue date : 18/12/2025
	Extreme Gear Lube SAE 85W-90	Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice	: First aider: Pay attention to self-protection. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance. Treat symptomatically.
Inhalation	: Remove casualty to fresh air and keep warm and at rest. In case of doubt or persistent symptoms, consult always a physician.
Skin contact	: Remove contaminated clothing and shoes. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.
Eyes contact	: Rinse immediately carefully and thoroughly with eye-bath or water. In case of doubt or persistent symptoms, consult always a physician.
Ingestion	: Rinse mouth thoroughly with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: The following symptoms may occur: Irritation.
Skin contact	: May cause an allergic skin reaction. The following symptoms may occur: Redness.
Eyes contact	: The following symptoms may occur: Irritation.
Ingestion	: The following symptoms may occur: May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: carbon dioxide (CO ₂), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards	: Not flammable. Heating will cause a rise in pressure with a risk of bursting.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO ₂). nitrogen oxides (NO _x) and sulphur oxides. Phosphorus oxides. Aldehydes.

5.3. Advice for firefighters

Firefighting instructions	: Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
Other information	: Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

	SAFETY DATA SHEET	Page : 5 / 24
		Revision nr : 4.0
		Issue date : 18/12/2025
	Extreme Gear Lube SAE 85W-90	Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel : Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Do not breathe vapours. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment.

Hygiene measures : Keep good industrial hygiene. Wash hands immediately after handling the product. When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs. Separate working clothes from town clothes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage.

	SAFETY DATA SHEET	Page : 6 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

Packaging materials : Keep only in the original container.

7.3. Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Naphtha (petroleum), hydrotreated heavy (conc. benzene > 0,1%) (64742-48-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	White spirit Type 3
IOEL TWA	116 mg/m ³
	20 ppm
IOEL STEL	290 mg/m ³
	50 ppm
Remark	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	300 mg/m ³ (varnish)
NDSch (OEL STEL)	900 mg/m ³ (varnish (Benzin))
Portugal - Occupational Exposure Limits	
OEL chemical category	A2 - Suspected Human Carcinogen
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m ³
	50 ppm
KZGW (OEL STEL)	600 mg/m ³
	100 ppm

ethyl acrylate (140-88-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylacrylate
IOEL TWA	21 mg/m ³
	5 ppm
IOEL STEL	42 mg/m ³
	10 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU

	SAFETY DATA SHEET	Page : 7 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

ethyl acrylate (140-88-5)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	20 mg/m ³
	5 ppm
MAK (OEL STEL)	40 mg/m ³
	10 ppm
OEL chemical category	Skin notation, Skin sensitizer
Belgium - Occupational Exposure Limits	
Local name	Acrylate d'éthyle # Ethylacrylaat
OEL TWA	21 mg/m ³
	5 ppm
OEL STEL	42 mg/m ³
	10 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Bulgaria - Occupational Exposure Limits	
OEL TWA	21 mg/m ³
	5 ppm
OEL STEL	42 mg/m ³
	10 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	21 mg/m ³
	5 ppm
KGVI (OEL STEL)	42 mg/m ³
	10 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	21 mg/m ³
	5 ppm
OEL STEL	42 mg/m ³
	10 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	20 mg/m ³
OEL chemical category	Potential for cutaneous absorption, Sensitizer
Denmark - Occupational Exposure Limits	
OEL TWA	21 mg/m ³

	SAFETY DATA SHEET	Page : 8 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

ethyl acrylate (140-88-5)	
	5 ppm
OEL STEL	42 mg/m ³
	10 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	21 mg/m ³
	5 ppm
OEL STEL	42 mg/m ³
	10 ppm
OEL chemical category	Sensitizer
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	21 mg/m ³
	5 ppm
HTP (OEL STEL)	42 mg/m ³
	10 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	21 mg/m ³ (restrictive limit)
	5 ppm (restrictive limit)
VLEP CT (OEL STEL)	42 mg/m ³ (restrictive limit)
	10 ppm (restrictive limit)
Germany - Occupational Exposure Limits (TRGS 900)	
Occupational exposure limit value (mg/m ³) (TRGS900)	8,3 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Occupational exposure limit value (ppm) (TRGS900)	2 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation, Skin sensitization
Gibraltar - Occupational Exposure Limits	
OEL TWA	21 mg/m ³
	5 ppm
OEL STEL	42 mg/m ³
	10 ppm
Greece - Occupational Exposure Limits	
OEL TWA	21 mg/m ³
	5 ppm

	SAFETY DATA SHEET	Page : 9 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

ethyl acrylate (140-88-5)	
OEL STEL	42 mg/m ³
	10 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	21 mg/m ³
CK (OEL STEL)	42 mg/m ³
OEL chemical category	Sensitizer, Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	20 mg/m ³
	5 ppm
OEL STEL	41 mg/m ³
	10 ppm
OEL chemical category	Sensitizer, Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	21 mg/m ³
	5 ppm
OEL STEL	42 mg/m ³
	10 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	21 mg/m ³
	5 ppm
TPRV (OEL STEL)	42 mg/m ³
	10 ppm
OEL chemical category	Sensitizer
Luxembourg - Occupational Exposure Limits	
OEL TWA	21 mg/m ³
	5 ppm
OEL STEL	42 mg/m ³
	10 ppm
Malta - Occupational Exposure Limits	
OEL TWA	21 mg/m ³
	5 ppm
OEL STEL	42 mg/m ³

	SAFETY DATA SHEET	Page : 10 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

ethyl acrylate (140-88-5)	
	10 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	21 mg/m ³
	5 ppm
TGG-15min (OEL STEL)	42 mg/m ³
	10 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	20 mg/m ³
NDSch (OEL STEL)	40 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	21 mg/m ³ (indicative limit value)
	5 ppm (indicative limit value)
OEL STEL	42 mg/m ³ (indicative limit value)
	10 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	21 mg/m ³
	5 ppm
OEL STEL	42 mg/m ³
	10 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	21 mg/m ³
	5 ppm
NPHV (OEL C)	42 mg/m ³
OEL chemical category	Sensitizer
Slovenia - Occupational Exposure Limits	
OEL TWA	21 mg/m ³
	5 ppm
OEL STEL	42 mg/m ³
	10 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	21 mg/m ³
	5 ppm

	SAFETY DATA SHEET	Page : 11 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

ethyl acrylate (140-88-5)	
VLA-EC (OEL STEL)	42 mg/m ³
	10 ppm
OEL chemical category	Sensitizer
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	20 mg/m ³
	5 ppm
KGV (OEL STEL)	40 mg/m ³
	10 ppm
OEL chemical category	Sensitizer
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	21 mg/m ³
	5 ppm
WEL STEL (OEL STEL)	42 mg/m ³
	10 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	21 mg/m ³
	5 ppm
Korttidsverdi (OEL STEL)	42 mg/m ³ (value from the regulation)
	10 ppm (value from the regulation)
OEL chemical category	Skin notation, Carcinogen, Allergenic substance
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	10 mg/m ³
	2,5 ppm
KZGW (OEL STEL)	42 mg/m ³
	10 ppm
OEL chemical category	Sensitizer
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	5 ppm
ACGIH® TLV® STEL	15 ppm
ACGIH® chemical category	Not Classifiable as a Human Carcinogen

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Personal air monitoring. Room air monitoring.

	SAFETY DATA SHEET	Page : 12 / 24
		Revision nr : 4.0
		Issue date : 18/12/2025
	Extreme Gear Lube SAE 85W-90	Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Additional information : Personal air monitoring :. Room air monitoring. Recommended monitoring procedures

8.1.5. Control banding

No additional information available

8.2. Exposure controls

Engineering measure(s)	: Provide adequate ventilation. Organisational measures to prevent/limit releases, dispersion and exposure. See Section 7 for information on safe handling .
Personal protective equipment	: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Hand protection	: Wear chemically resistant gloves (tested to EN374). The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Use splash goggles when eye contact due to splashing is possible (EN 166)
Body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: ABEK + P (EN 141). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)
Thermal hazard protection	: Not required for normal conditions of use. Use dedicated equipment.
Environmental exposure controls	: Avoid release to the environment. Comply with applicable Community environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Dark amber.
Appearance	: Liquid.
Odour	: mild.
Odour threshold	: No data available
Melting / freezing point	: No data available
Freezing point	: Not available
Initial boiling point and boiling range	: No data available
Flammability	: Not applicable,liquid

	SAFETY DATA SHEET	Page : 13 / 24
		Revision nr : 4.0
		Issue date : 18/12/2025
	Extreme Gear Lube SAE 85W-90	Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 182 °C (PMCC), ASTM D93
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
pH value	: No data available
Kinematic viscosity	: 141 mm ² /s (37,8 °C)
Solubility	: Water: Insoluble
Partition coefficient n-octanol/water (Log Kow)	: Not available
Partition coefficient n-octanol/water	: No data available
Vapour pressure	: No data available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 0,892 (15,6 °C)
Vapour density	: No data available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content	: < 3 g/l
Bulk density	: 889,1 kg/m ³

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal processing. Reference to other sections 10.4 & 10.5.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat. See Section 7 for information on safe handling.

	SAFETY DATA SHEET	Page : 14 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

10.5. Incompatible materials

Strong oxidizing agents. Acids. See Section 7 for information on safe handling.

10.6. Hazardous decomposition products

Reference to other sections 5.2.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Naphtha (petroleum), hydrotreated heavy (conc. benzene > 0,1%) (64742-48-9)	
LD50/oral/rat	> 6000 mg/kg (Source: EPA_HP.V)
LD50/dermal/rabbit	> 5000 mg/kg (Source: ECHA_API)
LC50/inhalation/4h/rat	> 8500 mg/m ³ (Exposure time: 4 h Source: EPA_HP.V)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LD50/oral/rat	> 15000 mg/kg (Source: EPA_HP.V)
LD50/dermal/rabbit	> 5000 mg/kg (Source: EPA_HP.V)
LC50/inhalation/4h/rat	> 2400 mg/m ³ (Exposure time: 4 h Source: EPA_HP.V)

Polysulfides, di-tert-Bu (68937-96-2)	
LD50/oral/rat	6500 mg/kg (Source: IUCLID)

Calcium Sulfonate (64521-08-0)	
LD50/oral/rat	> 5 g/kg
LD50/dermal/rabbit	> 2 g/kg
LC50/inhalation/4h/rat	> 5 mg/l

Amines, C12-14-tert-alkyl (68955-53-3)	
LD50/oral/rat	300 mg/kg (Source: NLM_CIP)

(Z)-octadec-9-enylamine (112-90-3)	
LD50/oral/rat	1689 mg/kg (Source: EPA_HP.V)
LD50, intraperitoneal, Mouse	888 mg/kg (Deutsche Zahnärztliche Zeitschrift. Vol. 35, Pg. 1070, 1980.)

ethyl acrylate (140-88-5)	
LD50/oral/rat	550 mg/kg (Source: JAPAN_GHS)

	SAFETY DATA SHEET	Page : 15 / 24
		Revision nr : 4.0
		Issue date : 18/12/2025
	Extreme Gear Lube SAE 85W-90	Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

ethyl acrylate (140-88-5)	
LD50/dermal/rat	1250 mg/kg
LD50/dermal/rabbit	1790 mg/kg (Source: JAPAN_GHS)
LC50/inhalation/4h/rat	9,14 mg/l
LC50/inhalation/4h/rat (ppm)	1410 ppm/4h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH value: No data available
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH value: No data available
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)

ethyl acrylate (140-88-5)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)

Naphtha (petroleum), hydrotreated heavy (conc. benzene > 0,1%) (64742-48-9)	
STOT-single exposure	May cause drowsiness or dizziness.

(Z)-octadec-9-enylamine (112-90-3)	
STOT-single exposure	May cause respiratory irritation.

ethyl acrylate (140-88-5)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)

(Z)-octadec-9-enylamine (112-90-3)	
STOT-repeated exposure	May cause damage to organs (gastro-intestinal tract, liver, immune system) through prolonged or repeated exposure.
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

Extreme Gear Lube SAE 85W-90	
Kinematic viscosity	141 mm ² /s (37,8 °C)

	SAFETY DATA SHEET	Page : 16 / 24
		Revision nr : 4.0
		Issue date : 18/12/2025
	Extreme Gear Lube SAE 85W-90	Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Kinematic viscosity	75,235 mm ² /s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

Other information : Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Naphtha (petroleum), hydrotreated heavy (conc. benzene > 0,1%) (64742-48-9)	
LC50 - Fish [1]	2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas Source: IUCLID)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LC50 - Fish [1]	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Polysulfides, di-tert-Bu (68937-96-2)	
LC50 - Fish [1]	250 – 500 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)
LC50 - Fish [2]	> 1000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static] Source: IUCLID)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Amines, C12-14-tert-alkyl (68955-53-3)	
LC50 - Fish [1]	1,3 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: ECHA)

	SAFETY DATA SHEET	Page : 17 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

(Z)-octadec-9-enylamine (112-90-3)	
LC50 - Fish [1]	0,11 mg/l

ethyl acrylate (140-88-5)	
LC50 - Fish [1]	4,6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)
LC50 - Fish [2]	2,31 – 2,7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	7,9 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	48 mg/l (Species: Desmodesmus subspicatus)

12.2. Persistence and degradability

Extreme Gear Lube SAE 85W-90	
Persistence and degradability	No additional information available.

ethyl acrylate (140-88-5)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

Extreme Gear Lube SAE 85W-90	
Partition coefficient n-octanol/water	No data available
Bioaccumulative potential	No additional information available.

Polysulfides, di-tert-Bu (68937-96-2)	
BCF - Fish [1]	(188 dimensionless (whole body w.w.)
Partition coefficient n-octanol/water	5,6 (at 20 °C (at pH 7)

ethyl acrylate (140-88-5)	
Bioconcentration factor (BCF)	2,07
Partition coefficient n-octanol/water	1,18 (at 25 °C)
Bioaccumulative potential	No bioaccumulation.

12.4. Mobility in soil

Extreme Gear Lube SAE 85W-90	
Mobility in soil	No data available

ethyl acrylate (140-88-5)	
Mobility in soil	Expected to be highly mobile in soil

	SAFETY DATA SHEET	Page : 18 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

ethyl acrylate (140-88-5)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3,9 – 85

12.5. Results of PBT and vPvB assessment

Extreme Gear Lube SAE 85W-90	
Results of PBT assessment	No data available

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Do not allow to enter into surface water or drains. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations.

Additional information : Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations.

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC) : This material and its container must be disposed of as hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

	SAFETY DATA SHEET	Page : 19 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

No data available

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

No data available

- Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Polysulfides, di-tert-Bu ; Amines, C12-14-tert-alkyl ; (Z)-octadec-9-enylamine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Extreme Gear Lube SAE 85W-90 ; Polysulfides, di-tert-Bu ; Amines, C12-14-tert-alkyl ; (Z)-octadec-9-enylamine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

	SAFETY DATA SHEET	Page : 20 / 24
		Revision nr : 4.0
		Issue date : 18/12/2025
	Extreme Gear Lube SAE 85W-90	Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content :< 3 g/l

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Detergent Regulation (648/2004/EC): Labelling of contents

15.1.2. National regulations

	SAFETY DATA SHEET	Page : 21 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

France

Occupational diseases			
Code	Description		
RG 65	Eczematiform lesions of allergic mechanism		
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide		
Installations classées			
No ICPE	Désignation de la rubrique	Code Régime	Rayon
na	Not Applicable	na	na

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Major Accidents Ordinance (12. BImSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

Waterbezwaarlijkheid : A (3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : Naphtha (petroleum), hydrotreated heavy (conc. benzene > 0,1%),Distillates (petroleum), solvent-dewaxed heavy paraffinic,Polysulfides, di-tert-Bu are listed

SZW-lijst van mutagene stoffen : Naphtha (petroleum), hydrotreated heavy (conc. benzene > 0,1%),Distillates (petroleum), solvent-dewaxed heavy paraffinic,Polysulfides, di-tert-Bu are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out
Polysulfides, di-tert-Bu

SECTION 16: Other information

Indication of changes:

3	Composition/information on ingredients	Update	
---	--	--------	--

Abbreviations and acronyms:

	ABM = Algemene beoordelingsmethodiek
--	--------------------------------------

	SAFETY DATA SHEET	Page : 22 / 24
		Revision nr : 4.0
	Extreme Gear Lube SAE 85W-90	Issue date : 18/12/2025
		Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Code LEL = Lower Explosive Limit/Lower Explosion Limit UEL = Upper Explosion Limit/Upper Explosive Limit REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	BTT = Breakthrough time (maximum wearing time)
	DMEL = Derived Minimal Effect level
	DNEL = Derived No Effect Level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate
	EWC = European waste catalogue
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	NA = Not applicable
	NOEC = No observed effect concentration
	NOEL = no-observed-effect level
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	N.O.S. = Not Otherwise Specified
	OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	PNEC = Predicted No Effect Concentration
	Quantitative structure-activity relationship (QSAR)
	STOT = Specific Target Organ Toxicity
	TWA = time weighted average
	VOC = Volatile organic compounds
	WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the : Safety Data Sheet: Supplier. ECHA (European Chemicals Agency), LOLI. datasheet

Training advice : Training staff on good practice. Manipulations are to be done only by qualified and authorised persons.

Other information : Classification - Assessment method: CLP Calculation method (Article 9).

Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1

	SAFETY DATA SHEET	Page : 23 / 24
		Revision nr : 4.0
		Issue date : 18/12/2025
	Extreme Gear Lube SAE 85W-90	Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Muta. 1B	Germ cell mutagenicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

	SAFETY DATA SHEET	Page : 24 / 24
		Revision nr : 4.0
		Issue date : 18/12/2025
	Extreme Gear Lube SAE 85W-90	Supersedes : 21/02/2023
		766-01-0276S (Original SDS: US 829338 Merc Racing Gear Lube was 259-7070K 2018)

EUH208	Contains Polysulfides, di-tert-Bu, Calcium Sulfonate, Amines, C12-14-tert-alkyl. May produce an allergic reaction.
--------	--

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.